

Espirocristal®

Monolayer, flexible, plasticised, transparent PVC hose especially for levelling in construction and piping liquids at low pressure.



Flexible, transparent PVC for food use.

Features

- For food use in accordance with European regulations EC 1935/2004 and EU 10/2011 (see declaration of conformity).
- Great flexibility and highly resistant to breakage when extended.
- Good chemical resistance associated with PVC's resistance chart.
- Recommended temperature for use between -10°C and 60°C.



DOMESTIC
USE



FOOD
USE



INDUSTRIAL
USE



CONSTRUCTION



LIGHT



HIGH QUALITY
CONTROL



FREE FROM
Cd / Pb / Ba

Applications

- Transfer of liquid food products that require food simulants A, B and C in OM2 conditions in accordance with Regulation EU 10/2011, such as wine, must, beer, vinegar and alcoholic liquids up to 20°.
- Industry in general and as a level in the construction industry.

Ø INT mm	Ø INT in	Ø EXT mm	WEIGHT g/m
2	5/64"	4	12±1
3	1/8"	5	16±1
4	11/64"	6	20±1
4	11/64"	7	32±2
5	11/64"	7	24±2
5	13/64"	8	39±2
6	1/4"	8	28±2
6	1/4"	9	45±2
6	1/4"	10	62±3
7	9/32"	9	32±2
7	9/32"	10	49±3
8	5/16"	10	35±2
8	5/16"	11	55±3
8	5/16"	12	78±4
8	5/16"	14	128±7
9	3/8"	12	61±3
10	3/8"	12	43±2
10	3/8"	13	67±3
10	3/8"	14	93±5
12	1/2"	15	78±4
12	1/2"	16	108±6
12	1/2"	18	174±9
13	5/8"	19	186±10
14	5/8"	18	124±6
15	5/8"	19	132±7
15	5/8"	20	169±9
16	5/8"	20	139±7
18	5/8"	23	198±10
18	5/8"	25	291±15
20	3/4"	25	218±11
25	1"	31	325±16
30	1" 1/8	38	526±26
50	2"	60	1065±54

Pressure at room temperature in laboratory. Nominal values without considering manufacturing tolerances.
Depending on technical developments, specifications may be modified without advance notice being given.
Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters