

Hidrotubo® Especial Termitas

Hose manufactured via the co-extrusion of flexible, blue PVC with a rigid, anti-shock PVC spiral in accordance with UNE-EN ISO 3994, with protection against termite attacks.



Features

- For industrial and sanitary use.
- The flexible PVC has a special formulation that prevents termite attacks without being toxic for the environment, in compliance with quality standard EN 118.
- Smooth internal and external surfaces. Highly flexible and light.
- External diameters adjusted for easy assembly on PVC and PE seal fittings.
- Hermetically sealed and resistant at joint up to pressure of 30 bar.
- Withstands temperatures between -10°C and 60°C.
- Hose with good chemical resistance associated with PVC's usual properties.
- Great resistance to waste water and chlorinated swimming pool water.



USE
IN POOLS



CONSTRUCTION



HIGH QUALITY
CONTROL



FREE FROM
Cd / Pb / Ba

Applications

- ▶ Discharge, hydro-sanitary piping, swimming pool filtration systems, hydro-massage bathtubs, drains, installed in areas susceptible to underground termite attacks.
- ▶ The ground must be free from termites prior to installation.

INT Ø mm	INT Ø in	EXT Ø mm	WEIGHT g/m	OPERATING PRESSURE bar	MINIMUM BURST PRESSURE bar	BENDING RADIUS mm	VACUUM m H ₂ O
42	1" 3/4	50	710	5	15	126	9
43	1" 3/4	50	685	5	15	129	9
55	2" 1/8	63	1000	5	15	165	9

Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances.
Depending on technical developments, specifications may be modified without advance notice being given.
Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters