

Mineflex®

Hose made from vinyl components and internally reinforced by a polyester mesh.



Features

- For industrial use.
- Highly flexible but resistant to folding, stretching, abrasion and accidental cuts.
- Stable against UV rays.
- Striated outer layer to facilitate resistance to the elements as well as wear and tear in very difficult working conditions.
- Resistant to a wide variety of chemical products and diverse weather events. Temperature range between -10°C and 60°C.
- Designed in accordance with European quality standard EN 694 and South African quality standard SANS 1086.



INDUSTRIAL
USE



HIGH
PRESSURES



HIGH QUALITY
CONTROL



FREE FROM
Cd / Pb / Ba

Applications

- General use in industrial environments, particularly in mining facilities.

INT Ø mm	INT Ø in	EXT Ø mm	WEIGHT g/m	OPERATING PRESSURE bar	MINIMUM BURST PRESSURE bar
10.5	3/8"	4	235	17	68
12.5	1/2"	5	355	17	68
20	3/4"	5.5	554	15	60
25	1"	5.5	658	14	56
32	1" 1/4	7	1080	10	40
40	1" 5/8	7.3	1370	9	36
51	2"	7.5	1720	9	36

Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances.
Depending on technical developments, specifications may be modified without advance notice being given.
Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters

