


Transvin® Phthalates Free Sliding

Phthalate-free PVC hose for transferring and transporting wine, alcoholic liquid foods (50% vol.), and milk products and their by-products. Manufactured in accordance with European legislation on raw materials for non-fatty food use. The hose's exterior is corrugated, with a rigid, sliding spiral to facilitate dragging.



Features

- For food use in accordance with European regulations EC 1935/2004 and EU 10/2011 (see declaration of conformity).
- The hose wall is smooth on the inside and corrugated on the outside.
- Good chemical resistance associated with PVC's resistance chart.
- Recommended temperature for use between -10°C and 60°C.



Applications

- Transfer of liquid food products that require food simulants A, B, C and D1 in OM2 conditions in accordance with Regulation EU 10/2011, such as wine, must, beer, vinegar and alcoholic liquids up to 50% vol. and milk products.

INT Ø mm	INT Ø in	WALL THICKNESS mm	WEIGHT g/m	OPERATING PRESSURE bar	MINIMUM BURST PRESSURE bar	BENDING RADIUS mm	VACUUM m H ₂ O
25	1"	3.5	390	8	24	125	9
30	1" 1/8	4	480	8	24	150	9
32	1" 1/4	4	500	8	24	160	9
35	1" 3/8	4.2	580	8	24	175	9
38	1" 1/2	4.2	670	8	24	190	9
40	1" 5/8	4.3	685	8	24	200	9
45	1" 3/4	4.5	850	8	24	225	9
51	2"	5	1020	8	24	250	9
55	2" 1/8	5	1190	7	21	275	9
60	2" 1/32	5.2	1260	7	21	300	9
63	2" 1/2	5.6	1320	7	21	310	9
70	2" 3/4	5.8	1615	6	18	350	9
76	3"	5.8	1700	6	18	375	9
80	3" 1/8	6	1870	5	15	400	9
90	3" 1/2	6.5	2156	5	15	450	9
102	4"	7	2680	4	12	500	9
110	4" 5/16	7.3	3060	4	12	550	9
120	4" 3/4	7.4	3320	4	12	600	9
127	5"	7.6	3485	4	12	625	9
152	6"	8.5	5355	3	9	760	9

Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances. Depending on technical developments, specifications may be modified without advance notice being given. Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters.