

Espirobil®

Multi-layer, plasticised PVC hose, reinforced with a polyester mesh. Specifically designed for use in aggressive working conditions due to its great resistance.



Features

- For industrial use and designed especially for the construction industry.
- Highly flexible and easy to handle.
- Striated outer layer in black to facilitate resistance to the elements as well as wear and tear in extremely difficult working conditions.
- Chemical resistance associated with PVC's resistance chart.
- Recommended temperature for use between -10°C and 60°C.



CONSTRUCTION



STRIATED



EASY TO USE



UV PROTECTION



ADVERSE SCENARIOS



HIGH QUALITY CONTROL



FREE FROM Cd / Pb / Ba

Applications

- ▶ Irrigation in very difficult working conditions.
- ▶ Construction, public works, quarries
- ▶ Irrigation and sprinkling in general, gardening, horticulture and floriculture.



INT Ø mm	INT Ø in	EXT Ø mm	WEIGHT g/m	OPERATING PRESSURE bar	MINIMUM BURST PRESSURE bar	ROLL LENGTH m
15	5/8"	21	210	8	24	50
19	3/4"	25	255	8	24	50
25	1"	32	385	8	24	50

Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances. Depending on technical developments, specifications may be modified without advance notice being given. Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters

