

Espirofuel®


Hose with special stability when dealing with hydrocarbons, gasoline and fuel, which makes it perfect for pumping and suctioning petroleum products and industrial oils.

Applications

► Suction and transfer of hydrocarbons and industrial oils.

116

ESPIROFUEL®



Internal, rigid, anti-shock PVC spiral reinforcement that affords it great consistency.

PVC material with special formulation for industrial oils and hydrocarbons.

Features

- For industrial use.
- Special formulation for industrial oils and hydrocarbons, diesel, gasoline, etc.
- The hose wall is smooth on the inside and corrugated on the outside.
- Good chemical resistance associated with PVC's resistance chart.
- Recommended temperature for use between -25°C and 70°C.



INDUSTRIAL USE



AGRICULTURAL USE



RESISTANT TO HYDROCARBONS



HIGH QUALITY CONTROL



FREE FROM Cd / Pb / Ba

ESPIROFLEX. MANUFACTURE OF FLEXIBLE HOSES



117

ESPIROFUEL®

INT Ø mm	INT Ø in	WALL THICKNESS mm	WEIGHT g/m	OPERATING PRESSURE bar	MINIMUM BURST PRESSURE bar	BENDING RADIUS mm	VACUUM m H ₂ O
19	3/4"	4.3	412	8	24	140	9
25	1"	4.3	550	7	21	160	9
30	1" 1/8	4.5	680	5	15	192	9
35	1" 3/8	4.5	750	5	15	224	9
40	1" 5/8	4.5	850	5	15	256	9
45	1" 3/4	5.5	1000	5	15	288	9
51	2"	5.5	1200	5	15	320	9
55	2" 1/8	5.5	1400	5	15	350	9
60	2" 1/4	6	1600	5	15	384	9
63	2" 1/2	6	1700	5	15	403	9
70	2" 3/4	6.3	1900	5	15	448	9
76	3"	6.5	2000	5	15	480	9
80	3" 1/8	6.7	2200	4	12	512	9
90	3" 1/2	7	2600	4	12	576	9
102	4"	7	3300	4	12	640	9
110	4" 5/16	7	3610	4	12	700	9

Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances. Depending on technical developments, specifications may be modified without advance notice being given. Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters.

ESPIROFLEX. MANUFACTURE OF FLEXIBLE HOSES

