

Espirogas®

Multi-layer, plasticised PVC hose, especially designed to resist aliphatic hydrocarbons, particularly butane and propane, at low pressures.



Features

- Complies with permeability, flexibility and flammability that ensure the product's great quality.
- Highly resistant to breakage when extended, traction (7.5 MPa) and pressure at high temperatures.
- Anti-knotting.
- Hose with product certification awarded by AENOR in accordance with UNE 53539.
- Available for piping liquefied petroleum gases (3rd family), including butane and propane, at low pressures, and for piping natural gas (2nd family version in white) at low pressures.



DOMESTIC
USE



HIGH QUALITY
CONTROL



FREE FROM
Cd / Pb / Ba

Applications

- Piping liquefied petroleum gases (LPG) and natural gas at low pressure.
- Supplying domestic apparatus with butane and outdoor heating.



INT Ø mm	INT Ø in	WALL THICKNESS mm	WEIGHT g/m	COLOUR	GAS TYPES
9	3/8"	3	138	Orange	Butane/Propane
15	5/8"	3.5	250	White	Natural gas



Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances. Depending on technical developments, specifications may be modified without advance notice being given. Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters