

Espiropres® 20 bar
Rubber

20 bar pressure hose made of nitrile rubber and PVC with special resistance to industrial oils



Features

- Industrial use.
 - Great flexibility and high resistance to breakage due to elongation.
 - Specially designed for the transfer of gasoline and its derivatives.
- Good chemical resistance, associated with the PVC resistance table.
 - The recommended temperature for use is between -10 °C and 60 °C.



INDUSTRIAL
USE



RESISTANT TO
HYDROCARBONS



CONSTRUCTION



LIGERA



HIGH QUALITY
CONTROL



FREE FROM
Cd / Pb / Ba

Applications

- Compressed air, pneumatic hammer, pneumatic drill.

INT Ø mm	INT Ø in	Ø EXT mm	WEIGHT g/m	OPERATING PRESSURE bar	MINIMUM BURST PRESSURE bar
6	11/64"	12	114	20	60
8	13/64"	15	170	20	60
10	1/4"	17	200	20	60
13	9/32"	21	285	20	60
16	5/16"	25	390	20	60
19	19	29	505	20	60
25	19	36	705	20	60

Pressure at room temperature in laboratory / Nominal values without considering manufacturing tolerances.
Depending on technical developments, specifications may be modified without advance notice being given.
Consult us for other diameters, colours and features. Ask our Sales Department about the minimum purchase amounts assigned to non-standard diameters